

U Bolt

Application:

U-Bolts are used to secure piping to structural members. When the piping is below the structural member, the U-Bolt provides vertical support and restricts lateral movement while allowing for axial movement. When the piping system is above the structural member, the U- Bolt restricts lateral movement and upward movement while allowing axial movement of the piping.

Construction:

U-Bolt is provided with four standard hex nuts and has a longer straight threaded length. Material : Mild steel
Maximum temperature : 399°C (750°F) Finish : Electro-Galvanized, Hot Dip Galvanized, Plain

						Nominal Pipe Size		Pipe Od In mm	Material Dimension in mm			Bolt Size
						Item Code	inch mm		Rod Dia	Height	Thread Length	
						SFUC-15	1/2" 15	21.3	21	95	50	M10
						SFUC-20	3/4" 20	26.7	27	77	50	M10
						SFUC-25	1" 25	33.4	34	85	50	M10
						SFUC-40	1-1/2" 40	48.2	48	100	50	M10
						SFUC-50	2" 50	60.3	60	110	50	M10
						SFUC-65	2-1/2" 65	73.0	76	127	50	M12
						SFUC-80	3" 80	88.9	89	140	50	M12
						SFUC-100	4" 100	114.3	115	165	50	M12

						SFUC-125	5"	125	141.3	140	190	50	M12
						SFUC-150	6"	150	168.3	168	220	50	M12
						SFUC-200	8"	200	219.1	219	295	75	M16
						SFUC-250	10"	250	273.3	273	370	100	M20
						SFUC-300	12"	300	323.8	324	420	100	M20
						SFUC-350	14"	350	355.6	356	455	100	M20
						SFUC-400	16"	400	406.4	406	505	100	M20
						SFUC-450	18"	450	457.2	457	555	100	M24
						SFUC-500	20"	500	508.0	508	605	100	M24
						SFUC-600	24"	600	609.6	610	710	100	M24

[Read More](#)

SKU:

Price:

Categories: [2.Clamps and Bolts](#)

Product Description
