



Pipe Hanger without Rubber (EPDM Lining)

Application:

PIPE HANGER is recommended for non-insulated stationary pipelines in a horizontal or vertical position. It can be used for supporting pipes along with the roof as well as walls.

Construction:

PIPE HANGER consists of piece of mild steel shaped to wrap around the pipe. The selection of the PIPE CLAMP depends upon the temperature of piping system and load to be carried. It permits installation before and after pipe is in place. Material : Mild steel Maximum temperature : 343° C (650°F) Finish : Electro-Galvanized

Product Table

Sr. No	Part Number	Trade Size	Pipe OD in inches	Pipe OD in mm
1	SFPC-050	1/2"	0.840	21.336
2	SFPC-075	3/4"	1.050	26.670
3	SFPC-100	1"	1.315	33.401
4	SFPC-125	1-1/4"	1.660	42.164
5	SFPC-150	1-1/2"	1.900	48.260
6	SFPC-200	2"	2.375	60.325
7	SFPC-250	2-1/2"	2.875	73.025
8	SFPC-300	3"	3.500	88.900
9	SFPC-350	3-1/2"	4.000	101.600
10	SFPC-400	4"	4.500	114.300
11	SFPC-600	6"	6.625	168.275
12	SFPC-800	8"	8.625	219.075
13	SFPC-100	10"	10.750	273.050

[Read More](#)

SKU:

Price:

Categories: [2.Clamps and Bolts](#)

