

Ground Rod



Copper Bonded Grounding Rods are made of excellent quality raw material & are globally accepted for doing Grounding with extended long life. Copper Bonded Grounding Rod is made from low carbon steel with a high tensile strength of at least 600 N/mm² which is molecularly bonded with 99.99% of pure electrolytic copper.

Product Features:

- It is long-lasting and free from maintenance
- Unique manufacturing process ensures uniform copper coating thickness
- It is easy to install and is unbreakable
- Corrosion free while providing the lowest resistance to ground
- Variable choices are manufactured in order to meet the customers demand
- Convenient installation and very beautiful appearance.
- Purity of the copper is 99.9%. Thus the conduct ability is very good.

ADVANTAGE :

- Corrosion resistant surface
- Excellent electrical and thermal conductivity
- Advanced technology with effective engineering
- Easy to install

INDUSTRIES:

- Electrical Industry
- Cements Industry
- Electrical Contractor
- Electrical Equipments
- Manufacturing Industries
- Sugar and paper Industry
- Petrol & Chemical Industry

Sr. No	Item Code	Rod Dia in mm	Total Length in mm	Thread Dia
1	SFGR-912	9.5	1200	Unthreaded
2	SFGR-1212	12.7	1200	9/16"
3	SFGR-1215	12.7	1500	9/16"

4	1218	12.7	1800	9/16"
5	SFGR-1224	12.7	2400	9/16"
6	SFGR-1230	12.7	3000	9/16"
7	SFGR-1412	14.2	1200	5/8"
8	SFGR-1415	14.2	1500	5/8"
9	SFGR-1418	14.2	1800	5/8"
10	SFGR-1424	14.2	2400	5/8"
11	SFGR-1430	14.2	3000	5/8"
12	SFGR-1712	17.2	1200	3/4"
13	SFGR-1715	17.2	1500	3/4"
14	SFGR-1718	17.2	1800	3/4"
15	SFGR-1724	17.2	2400	3/4"
16	SFGR-1730	17.2	3000	3/4"
17	SFGR-2524	25	2400	Unthreaded
18	SFGR-2530	25	3000	Unthreaded

[Read More](#)

SKU:

Price:

Categories: [4.Earthing](#)

Product Description
